





HDPE Fabricated Fitting Products Brochure

90° Elbow - Page 2

45° Elbow - Page 4

30°, 22.5° and 11.25° Elbow - Page 6

Equal Tee - Page 8

Equal Cross - Page 10

Lateral 45° Wye – Page 12

This publication is intended for use as a products offering brochure. The technical information in this publication does not constitute a guarantee or warranty for piping installations because the conditions of use are beyond individual controls. The user of this information assumes all risk associated with its use. P&F Distributors has made every reasonable effort to ensure accuracy, but the information in this publication may not be complete, especially for special or unusual applications. Changes to this publication may occur from time to time without notice. Please contact P&F Distributors to determine if you have the most current edition.

Revised 9/5/2025













HDPE Fabricated 90° Elbow

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further

Leak Free

Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range














Dimensions and weights are approximate and subjected to change. Please call for Sizes Not listed.

			Dimension (in)				
IPS Pipe Size	Nominal OD (in)	Dimension Ratio (DR)	R	F	XY	Weight (lbs)	
1.4	14.00	17	1.4	0	10	42	
14	14.00	11	14	14 8	19	62	
1.0	16.00	17	15	0	20	56	
16	16.00	11	15	8	20	84	
10	19.00	17	16 0 31	21	76		
18	18.00	11	16	8	21	113	
20	20.00	17	17	8	22	98	
20	20.00	11	1/	٥	22	147	
22	22.00	17	23	8	26	134	
22	22.00	11	23	٥	20	201	
24	24.00	17	24	Q	27	167	
24	24.00	11	24	8	27	250	
28	28.00	17	20	2 14	.4 42	352	
28	28.00	11	38 14	14		525	
30	30.00	17	38	14	43	410	
	30.00	11	30 1-	17		611	
32	32.00	17	38	3 14	43	473	
52	32.00	11	30	14	43	705	
34	34.00	17	38	20 11	14	44	542
	34.00	11	30	17	77	807	
36	36.00	17	38	14	44	616	
	30.00	11	36	17	77	917	
42	42.00	17	50	50 21	59	925	
72	72.00	11	30 21	-1	,,,	1,129	
48	48.00	17	51	21	61	1,244	
70	70.00	11	J.	-1	01	1,518	
54	54.00	17	51	21	62	1,244	
	37.00	11			02	1,518	













HDPE Fabricated Butt 45° Elbow

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further

Leak Free

Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range














Dimensions and weights are approximate and subjected to change. Please call for Sizes Not listed.

			Dimension (in)				
IPS Pipe Size	Nominal OD (in)	Dimension Ratio (DR)	R	F	XY	Weight (lbs)	
14	14.00	17	1.1	0	11	27	
14	14.00	11	14	14 8 2	11	40	
1.0	16.00	17	15		12	37	
16	16.00	11	15	8	12	55	
18	18.00	17	16	8	12	47	
10	18.00	11	10	٥	12	70	
20	20.00	17	17	0	12	60	
20	20.00	11	17 8	٥	8 12	90	
22	22.00	17	23	8	13	76	
22	22.00	11	23	٥	13	114	
24	24.00	17	24	Q	13	94	
24	24.00	11	24	24 8	13	141	
28	28.00	17	38	0 1/1	4 20	198	
20	28.00	11	38 14	14		295	
30	30.00	17	38	14	20	228	
	30.00	11	30	17	20	339	
32	32.00	17	38	14	21	266	
	32.00	11	36	30 14	21	396	
34	34.00	17	38	14	14	21	307
	34.00	11	50	17	21	458	
36	36.00	17	38	14 22	353		
	30.00	11	30	17		525	
42	42.00	17	50 21	21	21 30	353	
12	12.00	11				525	
48	48.00	17	51	21	31	742	
	10.00	11	J -			905	
54	54.00	17	51	21	32	775	
	3 1.00	11	J -		52	969	













HDPE IPS Fabricated Butt 30°, 22.5°, 11.25° Elbow

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further

Leak Free

Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range














Dimensions and weights are approximate and subjected to change. Please call for Sizes Not listed.

IPS Pipe	Nominal OD	Dimension Ratio	Di	mensi (in)	on	Weight	
Size	(in)	(DR)	R	F	XY	(lbs)	
10	10.00	17	17	17 6.5		11	
10	10.00	11	1 1/		8	17	
12	12.00	17	20	0	_	19	
12	12.00	11	20	8	9	28	
14	14.00	17	21	8	9	23	
14	14.00	11] 21	٥	9	35	
1.0	16.00	16.00	0	10	31		
16	16.00	11	24	8	10	46	
18	18.00	17	27	8	0 10	41	
18	18.00	11	2/	٥	10	60	
20	20.00	17	20	8	8 10	51	
20	20.00	11	30	0	10	75	
22	22.00	17	33	8	10	63	
22	22.00	11	33	8		93	
24	24.00	17	36	8	10	76	
24	24.00	11	30	0		113	
28	28.00	17	42	1/1	14 17	167	
20	28.00	11	72	14		249	
30	30.00	17	45	14 17	17	194	
30	30.00	11	73	17	1,	289	
32	32.00	17	48	1.1	14 17	223	
32	32.00	11	40	14		333	
34	34.00	17	51	14	14	17	255
J-	34.00	11	71	17	17	380	
36	36.00	17	- 54	14	4 18	286	
	30.00	11	34 14			426	
42	42.00	17	63	21	25	462	
72	72.00	11	55	-1	23	563	
48	48.00	26	72	21	26	617	
40	40.00	11	12		20	753	
54	54.00	26	81	21	26	652	
	34.00	11	01		20	799	

909.799.7800














HDPE Fabricated Equal Tee

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further

Leak Free

Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range
















Dimensions are approximate and subjected to change. Please call for Sizes Not listed.

Nominal Size	Mada francis	WDD	Approx. Di	mensions
Nominal Size	Made from SDR	WPR	Α	В
	7	252		
	9	200		7
3	11	160	17.5	7
•	17	100		
	7	252		
	9	200		_
4	11	160	18.5	7
-	17	100	10.5	
	7	252		
	9	200	7	
6	11	160	24.625	9
O	17	100	24.023	,
	7	252		
	9	200	7	
8	11	160	29.625	10.5
O	17	100	25.025	10.5
	7	252		
	9	200	1	
10	11	160	31.75	10.5
10	17	100	31./3	10.5
	7	252		
	9	200	-	
4.2	11	160	26.75	42
12	17	100	36.75	12
	7	252		
	9	200	-	
	11	160		
14	17	100	38	12
	7			
		252	_	
	9	200	_	
16	11	160	40	12
	17	100		
	7	252	_	
	9	200		
18	11	160	46	14
	17	100		
	7	252	_	
	9	200		
20	11	160	48	14
	17	100		
22	7	252		
	9	200		
	11	160	50	14
	17	100		
	7	252		
	9	200		
24	11	160	52	14
	17	100		














HDPE Fabricated Equal Cross

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further


Leak Free


Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range

















	I		Approx. Di	mensions
Nominal Size	Made from SDR WPR		A	В
	7	200		
	9	160		_
6	11	100	22.625	8
	17	80		
	7	200		
	9	160		8.5
8	11	100	25.625	
	17	80		
	7	200		
	9	160		
10	11	100	28.75	9
	17	80	1	
	7	200		
	9	160	31.75	9.5
12	11	100		
	17	80		
	7	200	33	9.5
	9	160		
14	11	100		
	17	80		
	7	200		
	9	160	35	9.5
16	11	100		
		80		
	17 7	200		
	9	160	_	10
18	11	100	38	
10	17		-	
	7	80 200		
	9	160	-	
20			43	11.5
20	11	100		
	17	80		
	7	200	-	
22	9	160	45 11	11.5
	11	100		11.5
	17	80		
	7	200	_	
24	9	160	47	11.5
24	11	100		
	17	80		














HDPE Fabricated Lateral 45° Wye

Fittings Simplified

Fabricated fitting products can be butt fused to PE pipe and/or molded fittings inline to create a complete piping system

Full Pressure Rating

Fabricated PE fittings are fully pressure rated to the listed dimensional ratio (DR) and do not need to be de-rated further

Leak Free

Fusion of PE fittings to PE pipe create a homogenous bond, restrained connection and a leak free piping system in which the joints are as strong as the parent material itself

Extreme Temperature Range














Dimensions are approximate and subjected to change. Please call for Sizes Not listed.

Nominal Size	Made from SDR	WPR	Approx. D	imensions B
	7	200	^	٠,
4	9	160	1	
	11	100	17	23
	17	80		
	7	200		
	9	160	-	
6	11	100	28	35
	17	80	1	
	7	200		
	9	160	-	
8	11	100	30	38
	17	80	1	
	7	200		
	9	160	1	
10	11	100	31	41
	17	80	-	
	7	200		
	9	160	36	4.0
12	11	100		48
	17	80		
	7	200		
	9	160	36	50
14	11	100		
	17	80		
	7	200		
	9	160		50
16	11	100	36	
	17	80	-	
	7	200		
	9	160	·	
18	11	100	41	56
	17	80	1	
	7	200		
	9	160		
20	11	100	51	69
	17	80	1	
	7	200		
	9	160	60	
22	11	100		78
	17	80	1	
	7	200		
	9	160	- 00	06
24	11	100	68	86
27	17	80	-	