


HDPE
Blind Flange, IPS
ANSI B16.5, B16.47 and AWWA C207



Dimensions and weights are approximate and subject to change. Please call for sizes not listed.

IPS Pipe Size	Nominal OD (in)	Pressure Class (psi)	Dimension (in)		Weight (Lbs)	Bolt	
			BCD	T		Diameter	Number
2"	2.375*	Low Pressure	4 3/4	1	2	5/8	4
3"	3.500*	Low Pressure	6	1	2	5/8	4
4"	4.500*	Low Pressure	7 1/2	1	3	5/8	8
6"	6.625*	Low Pressure	9 1/2	1	4	3/4	8
8"	8.625*	Low Pressure	11 3/4	1	6	3/4	8
10"	10.750*	Low Pressure	14 1/4	1 1/2	9	7/8	12
12"	12.750*	Low Pressure	17	1 1/2	13	7/8	12
14"	14.000*	Low Pressure	18 3/4	2	15	1	12
16"	16.000*	Low Pressure	21 1/4	2	19	1	16
18"	18.000*	Low Pressure	22 3/4	2	22	1 1/8	16
20"	20.000*	Low Pressure	25	2	20	1 1/8	20
22"	22.000*	Low Pressure	27 1/4	2	30	1 1/4	20
24"	24.000*	Low Pressure	29 1/2	2	36	1 1/4	20

* Meets AWWA

These Blind Flanges are ordinarily used for closure or night-capping of flanged pipes.

They are NOT fully pressure rated.

Without the use of a metal back up blind flange, the HDPE may leak between bolt-holes at moderate pressures. Always use metal washers.

San Francisco	511 Tunnel Avenue, Brisbane, CA 94005	415-467-4630	FAX 415-467-1010
Los Angeles	1304 E. San Bernardino Ave., San Bernardino, CA 92408	909-799-7800	FAX 909-799-5558
Bakersfield	5221 Gilmore Ave., Bakersfield, CA 93308	661-326-7800	FAX 661-326-7805
Reno	675-B Edison Way, Reno, NV 89502	775-856-1888	FAX 775-856-1844